

UNITEN 2


WIDIA/WIDIA/NBR

X1P1X3X3P1 (X6336)

EN 12756 compliant

Rotation: uni directional right
Stationary ring: with O-ring
Max pressure: 16 bar
Temperature: -25° max +90°

Use: non-acidic dirty liquids



ROTEN®



Dimensions mm				SHORT TAIL				EXTENDED TAIL			
SHAFT	ROTATING PART	STATIONARY RING		COMPLETE MECHANICAL SEAL		STATIONARY RING		COMPLETE MECHANICAL SEAL		STATIONARY RING	
d1	L	d7	l4	CODE	€	CODE	€	CODE	€	CODE	€
10	15	21	7	0114210	121.67	0164210	56.08	0114210C.L.	132.75	0164210C.L.	69.88
12	18	23	7	0114212	126.67	0164212	58.27	0114212C.L.	138.35	0164212C.L.	69.88
14	22	25	7	0114214	144.16	0164214	66.30	0114214C.L.	157.51	0164214C.L.	79.57
16	23	27	7	0114216	150.03	0164216	68.49	0114216C.L.	163.64	0164216C.L.	82.03
18	24	33	10	0114218	93.52	0164218	74.64	0114218C.L.	179.78	0164218C.L.	98.67
20	25	35	10	0114220	103.62	0164220	82.35	0114220C.L.	199.00	0164220C.L.	98.67
22	25	37	10	0114222	122.56	0164222	98.13	0114222C.L.	133.76	0164222C.L.	117.72
24	27	39	10	0114224	132.98	0164224	106.16	0114224C.L.	255.39	0164224C.L.	127.14
25	27	40	10	0114225	246.56	0164225	111.94	0114225C.L.	268.79	0164225C.L.	134.04
28	29	43	10	0114228	164.83	0164228	132.11	0114228C.L.	179.80	0164228C.L.	158.33
30	30	45	10	0114230	187.55	0164230	150.04	0114230C.L.	204.61	0164230C.L.	179.89
32	30	48	10	0114232	192.78	0164232	153.94	0114232C.L.	370.49	0164232C.L.	184.60
33	39	48	10	0114233	380.17	0164233	171.60	0114233C.L.	414.34	0164233C.L.	205.58
35	39	50	10	0114235	401.59	0164235	181.82	0114235C.L.	437.69	0164235C.L.	217.72
38	42	56	13	0114238	433.82	0164238	196.48	0114238C.L.	473.00	0164238C.L.	235.44
40	42	58	13	0114240	491.07	0164240	223.56	0114240C.L.	524.39	0164240C.L.	256.68
43	47	61	13	0114243	597.78	0164243	271.39	0114243C.L.	638.35	0164243C.L.	311.74
45	47	63	13	0114245	646.42	0164245	287.98	0114245C.L.	675.32	0164245C.L.	316.71

- to place an order for a mechanical seal with left-handed rotation, add SX after the code. For example: 0114238SX (5% increase on the price list)
- packages with stationary ring: individual pieces

INFO: On pages 12 and 13 there are EPDM and FPM o-rings available.

