

EXPANDABLE BRAIDED SLEEVING

UL224 VW-1



| Description | Pieces (m) / Pack | Code | €/m |
|----------------------|-------------------|----------------|-------------|
| BRAIDED SLEEVE 3 MM | 100 | 0812503 | 0.52 |
| BRAIDED SLEEVE 4 MM | 100 | 0812504 | 0.53 |
| BRAIDED SLEEVE 6 MM | 100 | 0812506 | 0.62 |
| BRAIDED SLEEVE 8 MM | 100 | 0812508 | 0.69 |
| BRAIDED SLEEVE 10 MM | 100 | 0812510 | 0.80 |
| BRAIDED SLEEVE 12 MM | 100 | 0812512 | 1.05 |
| BRAIDED SLEEVE 15 MM | 100 | 0812515 | 1.10 |
| BRAIDED SLEEVE 20 MM | 100 | 0812520 | 1.25 |
| BRAIDED SLEEVE 25 MM | 100 | 0812525 | 1.60 |
| BRAIDED SLEEVE 30 MM | 100 | 0812530 | 1.80 |
| BRAIDED SLEEVE 40 MM | 100 | 0812540 | 2.30 |
| BRAIDED SLEEVE 50 MM | 100 | 0812550 | 2.60 |

GENERAL CHARACTERISTICS:

Made of polyester single threads, it is particularly suitable for the protection of electrical wires and cables. Self-extinguishing, insulating, resistant to rubbing and marine atmospheres. On request, diameters up to 90 mm can be made.

COLOUR: black

OPERATING TEMPERATURE: -50°C : +150°C

MAX TEMPERATURE FOR BRIEF PERIODS: +220°C

MELTING TEMPERATURE: +260°C

DIRECTIVES: 2002/95/CE RoHS - Flammability UL224 VW-1

On request, it can also be provided with self-extinguishing level UL94-V0