

CAPACITORS WITH ELECTRONIC DISCONNECTOR


DUCATI energia s.p.a.


CAPACITY μF	$\varnothing$	HEIGHT	CODE	€/pc
20	45	118	0601520	47,97
25	45	118	0601525	48,66
30	45	118	0601530	48,99
35	45	118	0601535	49,99
40	50	118	0601540	50,75
45	50	118	0601545	52,02
50	55	120	0601550	52,65
60	55	120	0601560	56,45
65	55	120	0601565	57,42
70	55	120	0601570	58,04
75	60	120	0601575	58,63
80	60	120	0601580	59,32

dimensions in mm

TECHNICAL FEATURES:

Motor power supply: 220 - 240 V

Frequency: 50-60Hz

 Capacity tolerance: $\pm 5\%$

Working voltage: 320V-480V

(Vrms measured with engine without load at the ends of the starting capacitor)

Recommended repetition interval: 6 seconds

Maximum number of starts: 6 per minute

Climatic category: -25/85/21

Protection level: IP54

Housing and cover: in self-extinguishing V" grade plastic, in conformity to UL94.

 Two-pole cable 300 mm long, PVC insulation, 2x0,75 mm², type H05V2V2-F, max temperature 90°C

MECHANICAL SEALS

PUMPS

FANS

MOTORS

INSULATION

EQUIPMENT

MOTOR SPARES

TOOL SPARES

SWITCHES